

OIL QUICK COUPLINGS

RACCORD RAPIDE HUILE

SCHNELLKUPPLUNGEN FÜR HYDRAULIK

Interchangeability:
FASTER NV SERIES - INTERTRACO
N SERIES, STUCCHI IR SERIES
According to request is manufactured
from AISI 303 and AISI 316TI

Temperature Range:
-25°C +125°C (-13°F +257°F)

Working Pressure:
0 - 300 bar (0 - 4350 PSI)

Standard Version:
Steel
Zinc Plated
Seals - Nitrile (NBR)

Material:
Coupler Body - Zinc Plated
Sleeve - Steel
Valve - Steel
Springs - Steel
Balls - Stainless Steel
Seals - BUNA (NBR)

Interchangeabilité:
**FASTER NV SERIES - INTERTRACO
N SERIES, STUCCHI IR SERIES**
**Selon la demande est fabriqué
de AISI 303 et AISI 316TI**

Température d'utilisation:
-25°C +125°C (-13°F +257°F)

Pression de Service:
0 - 300 bar (0 - 4350 PSI)

Version Standard:
Acier
Zingué
Joint - Nitrile (NBR)

Matière:
Corps de Coupleur - Zingué
Bague - Acier
Clapet - Acier
Ressort - Acier
Billes - Acier Inoxydable
Joint - BUNA (NBR)

Kompatibilität:
FASTER NV SERIES - INTERTRACO
N SERIES, STUCCHI IR SERIES
Auf Anfragen in Edelstahl:
AISI 303 und AISI 316TI

Temperaturbereich:
-25°C +125°C (-13°F +257°F)


Betriebsdruck:
0 - 300 bar (0 - 4350 PSI)

Standardversion:
Stahl
verzinkt
Dichtungen - Nitril (NBR)

Material:
Kupplungsgrundkörper - verzinkt
Hülse - Stahl
Ventil - Stahl
Federn - Stahl
Kugeln - Edelstahl
Dichtungen - BUNA (NBR)

FEMALE THREADED COUPLER / COUPLEUR RAPIDE FEMELLE TARAUDÉ

KUPPLUNG MIT INNENGEWINDE




Th (BSPP)	Ø D	L	CH	Part-number
1/4	27	50	19	R14
3/8	33	59.5	24	R38
1/2	38	66	27	R12
3/4	47.5	84	34	R34
1"	55	96.5	41	R100
1" 1/4	70	115	50	R114
1" 1/2	84	127.5	60	R112



FEMALE THREADED PLUG / COUPLEUR RAPIDE MÂLE TARAUDÉ

NIPPLE MIT INNENGEWINDE



Th (BSPP)	Ø D	ØD1	L	CH	Part-number
1/4	21	14.2	33	19	P14
3/8	27	19	39	24	P38
1/2	30	20.5	44	27	P12
3/4	38	26.9	55	36	P34
1"	45	31.4	63	41	P100
1" 1/4	55.5	-	73	50	P114
1" 1/2	66	-	83	60	P112

